

DOOR LOOP TYPE SD

Door loop type SD 50 is a wire conduit to protect exposed wires in order not to be damaged.

PROPERTIES

: Door loops are **protective** means for **guiding wires from the frame to doors with installed electrical devices** such as electric locks.


: Can be attached to a tapered panel with a width of 25 mm.

: It needs a **minimum of space**. It is suitable for narrow door spaces due to its small design.


: **Easy to maintain**.



DIMENSIONS



STRUCTURE DIAGRAM



TECHNICAL SPECIFICATION

Model:	SD 50
Connector material:	Zinc Alloy
Conduit material:	Galvanized iron
Inner diameter of the conduit:	9,5 mm
Outside diameter of the conduit:	12,5 mm
Length of the conduit:	400 mm
Total length:	500 mm
Weight:	222 g

Model:	SD 50-A
Connector material:	Zinc Alloy
Conduit material:	Stainless steel
Inner diameter of conduit:	9,5 mm
Outside diameter of the conduit:	12,5 mm
Length of the conduit:	400 mm
Total length:	500 mm
Weight:	212 g



The leader in door opening solution
www.zadlabacipruchocky.cz
www.acssolution.cz

Updated: 9/2022 | ACS Solution s.r.o. Specifications are subject to change without prior notice. Note: The colors of the images in this brochure may differ from the actual colors.